

Introducing

The New Perlick Single Door Freezer



Model F24SS with
optional casters

Perlick's New Front Vented Single Door Freezer offers four great models designed to chill your glassware in an attractive front-opening style cabinet that provides versatility and features like no one else in the industry.



Perlick
CORPORATION



Perlick Features

- ◆ Front vented compressor
- ◆ Self-closing right hinge door standard with reversible door hinging
- ◆ Push button hot gas defrost system
- ◆ Interior floor drain removes melting ice during defrost cycle
- ◆ Heavy duty stainless steel hinges
- ◆ Vinyl-coated shelves (2) and bottom rack
- ◆ Self contained, no plumbing required
- ◆ Efficient, balanced refrigeration system
- ◆ Quiet running, high efficiency compressor
- ◆ Stainless steel interior standard

Specifications

Models	F24NB Black door w/no finished top F24NS Stainless steel door w/no finished top F24SB Black door finished top F24SS Stainless steel door finished top
Length (mm)	24" (610)
Interior Cu. Ft. (m³)	4.9" (0.14)
Shelving	Floor shelf and two shelves included
Glass capacity	86 Glasses (based on use of 3" dia. glasses on standard shelving).
Amps	2.0
Weight lbs. (kg)	145 (54)
Interior	Both models have stainless steel inner liner. Includes two adjustable vinyl-coated shelves plus a bottom shelf.
Exterior	Models F24NB and F24NS have galvanized steel back, top and sides. Models F24SB and F24SS have 20ga stainless steel top and sides. Back is galvanized steel. Both models have 20ga stainless steel front. Doors are either black powder coat, 20ga CRS or 20ga stainless steel. Bottom is 18ga galvanized steel with 20ga stainless grille.
Electrical	115V, 60Hz., 1 phase. Furnished with 6 foot rubber plug-in cord.
Plumbing	No plumbing required. Moisture drains to self evaporating condensate pan in machinery compartment.
Insulation	2 inch foamed-in-place polyurethane insulation.
Temp. Range	Adjustable from -10° to +10° F (-23° to +12° C).
Refrigeration	R134a capillary tube/type with hermetic condensing unit. Front access for condenser and cleaning.
Ventilation	Front vented.
Defrost system	Solid-state, push button hot gas defrost system, manually initiated at the end of each day, automatically terminates after six hours. Evaporator automatically defrosts every 4 hours for approximately 20 minutes (time/Temperature terminated).
Optional Accessories	<ul style="list-style-type: none"> • Set of 4 casters (3³/₄" high) P/N 65428. • Set of 4 adjustable legs (6" - 7¹/₄" high) P/N 66423.



Push button defrost system



Front vented compressor



Handle with reversible door hinging



Heavy duty stainless steel hinges



3 levels of vinyl-coated shelves



8300 West Good Hope Road • Milwaukee, WI 53223
Phone: 800-558-5592 • Fax: 414-353-7069
E-Mail: Perlick@Perlick.com • www.perlick.com